

DIXONS

VARIO 2228

PORTABLE AUTOCLAVE



- Variable Cycle Temperature
- Variable Cycle Time
- Four Preset Cycles
- Variable Cycle Stored In Permanent Memory For Instant Recall
- Soft Touch Control Pad
- Wipe Clean Surface
- Temperature Range 100°C - 121°C
- Time Range 0 - 99 minutes
- LED System Status Indicators
- Compact And Fully Portable
- Simple And Safe Use
- Domestic Electricity Supply
- No Plumbing Needed
- Minimal Maintenance Required
- Electrically Safe To BS3456
- Lid Locking Safety To H&SE PM73
- Produced Under ISO 9001
- Suitable For Culture Media
- 316 Stainless Steel Construction
- 22 Litre Capacity
- 280mm Internal Diameter
- 21.0Kg Net Weight
- CE Marked



DIXONS SURGICAL INSTRUMENTS LTD, 1 ROMAN COURT, HURRICANE WAY
WICKFORD BUSINESS PARK, WICKFORD, ESSEX, SS11 8YB, UK
TEL: +44 (0)1268 764614 - FAX: +44 (0)1268 764615
EMAIL: info@dixons-uk.com - WEB: <http://www.dixons-uk.com>

The VARIO 2228 Portable Autoclave

The VARIO 2228 is heated by a single internal element. This is available for use with 230V or 110V electrical supplies. Please indicate the required voltage when ordering. The temperature is controlled by the VARIO time and temperature control and PT100 probe. The VARIO 2228 is fitted with an automatic cut-out to prevent it boiling dry. Every autoclave is electrically tested in compliance with BS3456 Part 101 1987.

The VARIO time and temperature control features four preset and one variable cycle. The variable cycle is stored in permanent memory so that it can be instantly recalled for the next use. The control shows a countdown of sterilisation time and current temperature at all times.

Operation is very simple. The cycle temperature and time are selected by pressing either one of the four preset cycle buttons or the variable cycle button. If the variable cycle is chosen the temperature and time are then set to the values required. The Start button is then pressed and the unit automatically runs through the sterilisation cycle unattended. At the end of sterilisation an audible sound is given to allow the user to drain off the water, if the drying vacuum cycle is required. The unit then cools until it reaches a safe temperature for the contents to be removed, at which point another audible sound is given.

The VARIO 2228 is made from stainless steel with a polished exterior for easier cleaning. The lid is removable for full width access. Items to be sterilised can be placed in the inner liner provided with the machine. Alternately, Dressing Drums and Wire Mesh Baskets are available.

The lid locking device is comprised of six wing nuts and six locking lugs. This ensures that the lid cannot be opened while the vessel is under pressure. After the sterilising period, a condensing vacuum is drawn to aid drying. This is particularly useful for dressings and drapes.

The VARIO 2228 is particularly suitable for destructive sterilisation. The operator is not restricted to a set sterilising period. This can be adjusted to suit the application.

The VARIO 2228 comes complete with:

- Inner Liner with Handles
- Easy to follow Users Manual
- Manufacturers Safety Test Certificate
- Manufacturers One Year Guarantee (this does not affect your statutory rights)

Technical Specification

Model	:	VARIO 2228
Capacity	:	22 Litres
Dimensions	:	Internal Diameter : 280 mm Internal Height (useable) : 360 mm Internal Height (total) : 395 mm
Material	:	Stainless Steel 316
Heat Source	:	Internal Electric Element 230V / 110V - AC 50Hz - 2.0kW Electronic Thermostatic Control
Design Pressure	:	1.3 bar (18 psi)
Design Temperature	:	0 - 125°C
H T Pressure	:	2.0 bar (30 psi)
S W Pressure	:	1.3 bar (18 psi)
Maximum Working Temperature	:	121°C
Variable Temperature	:	100°C - 121°C
Variable Time	:	1 minute - 99 minutes
Preset Cycles	:	30 minutes @ 115°C 15 minutes @ 121°C 30 minutes @ 121°C 60 minutes @ 115°C
VARIO Control Dimesions	:	Width : 195 mm Depth : 120 mm Height : 65 mm
VARIO Control Weight	:	0.75Kg
Complies With	:	H&SE PM73 (Lid Locking Devices) BS3456 Part 101 1987 (Electrical Safety) CE Marked in compliance with EMC regulations 1992
Overall Dimensions	:	Width : 370 mm Depth : 390 mm Height : 600 mm
Net Weight	:	21.0 Kg